

SEBANG

SEBANG GLOBAL BATTERY

TECHNICAL DATASHEET

Date




2025.01.22

Prepared by

Checked by

Approved by

Type	LN5	Created:	2025.01.22
Type(GBC)	GB 60044	Modified:	



PERFORMANCES			CONTAINER		
Voltage(V):	12	Nominal	Type:	LN5	EN
C20(Ah):	100		Hold Down:	Yes	B3
RC(min):	180		H.D.Adapter:	No	
Cold Cranking Ampere(A):	800	EN	COVER		
Charge Acceptance(A):	10		Type:	Flat/Sealed Type	
Water Consumption(g/Ah):	LOW(L)	4.0 g/Ah ↓	Polarity:	(-, +)	Cell layout
Plates per Cell(pcs):	20		Terminals:	Standard Large	
Pos./ Grid Alloy:	Exp. / Pb-Ca-Sn		Terminal Adapter:	No	
Neg./ Grid Alloy:	Exp. / Pb-Ca		Magic Eye:	Yes	
Separator:	PE Enveloping		Degassing system:	Yes	
			Flame Arrestor:	Yes	
			Vent Block Pin:	No	
WEIGHT AND STD.DIMENSIONS					
BatteryWeight(kg):	22.2	with acid			
Length(mm):	353				
Width(mm):	175		PLUGS		
Height(mm):	-		Type:	No	Vent Sealed
Total Height(mm) :	190		HANDLES		
			Type:	2x Integrated	
			OTHERS		
			Degassing Tube:	No	

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by GBC