

LITHIUM IRON PHOSPHATE BATTERY

ELECTRICAL SPECIFICATIONS

Nominal Voltage	12.8 V
Nominal Capacity	140 Ah
Capacity @ 0.2C	>290 min
Energy	1792 Wh
Resistance	<20 mΩ
Efficiency	99%
Self Discharge	<3% per Month
Maximum Modules in Series	4
Maximum Modules in Parallel	No limited

DISCHARGE SPECIFICATIONS

Maximum Continuous Discharge Current	100 A
Peak Discharge Current	450 A
Recommended Low Voltage Disconnect	11 V
PCM Discharge Voltage Cut-Off	10 V
Reconnect Voltage	12 V
Short Circuit Protection	Yes

TEMPERATURE SPECIFICATIONS

Discharge Temperature	-30 to 60 °C
Charge Temperature	-30 to 60 °C
Storage Temperature	-30 to 60 °C
PCM High Temperature Cut-Off	80 °C

DIMENSIONAL SPECIFICATIONS

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H)	306 x 168 x 216 mm
Weight	13.8 kg
Terminal Type	M8
Case Material	ABS
Enclosure Protection	IP44
Chemistry	LiFePO ₄

CHARGE SPECIFICATIONS

Recommended Charge Current	< 30 A
Maximum Charge Current	50A
Recommended Charge Voltage	14.2 V - 14.6 V
PCM Charge Voltage Cut-off	14.6V
Reconnect Voltage	14.0 V
Active Balance Current:	3.4V per cell and 30mV cell gap

BATTERY FUNCTIONS

Bluetooth	Yes
Active Cell balance	Yes
Heater	Yes
Victron CAN and NMEA2000	Yes

