


# Leisure and Marine SLI Battery



| Part information |                                   |
|------------------|-----------------------------------|
| Part No:         | 0092L40340                        |
| Short code:      | L4 034                            |
| Product line:    | L4                                |
| Technology:      | SLI - Starting-Lighting-Ignition* |
| EAN code:        | 4047025515702                     |



| Technical data                                     |                  |                 |                  |                          |
|----------------------------------------------------|------------------|-----------------|------------------|--------------------------|
| Nominal voltage:                                   | 12 V             |                 |                  |                          |
| Nominal capacity: (20 hr discharge down to 10.5 V) | C20              | 105 Ah          |                  |                          |
| Reserve capacity: (@ 25 A)                         | 193 Min          |                 |                  |                          |
| Cold cranking amps: (EN / -18°C U10s ≥ 7.5 V)      | 800 A            |                 |                  |                          |
| Group size:                                        | GR31             |                 |                  |                          |
| Short-time angle of inclination:                   | 55°              |                 |                  |                          |
| Permanent angle of inclination:                    | Up to 45°        |                 |                  |                          |
| Dimension:                                         | Length<br>330 mm | Width<br>174 mm | Ht. w/o terminal | Ht. w terminal<br>240 mm |
| Total battery weight: (approx., filled battery)    | 23,7 kg          |                 |                  |                          |
| Layout:                                            | 9                |                 |                  |                          |
| Terminal:                                          | 1                |                 |                  |                          |
| Base hold down:                                    | B01              |                 |                  |                          |
| Degassing:                                         | Central          |                 |                  |                          |

| Technical information |                                                                                                                                                 |        |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| Application:          | Leisure and Marine                                                                                                                              |        |
| Service:              | Absolutely maintenance-free                                                                                                                     |        |
| Standard charging:    | Charging voltage:                                                                                                                               | 14,4 V |
|                       | Charging current:                                                                                                                               | 10,5 A |
|                       | Charging pattern:                                                                                                                               | IU     |
| European standards:   | DIN EN 60095-1, -2, -4 Lead-acid starter batteries;<br>DIN EN 50342 Lead-acid starter batteries;<br>DIN 41 773, Charger with IU characteristics |        |

\*SLI (Starting-lighting-ignition): lead-acid starting-lighting-ignition/starter battery