
AGM Battery
For passenger vehicles

Part information	
Part No:	0092S5A050
Short code:	S5A05
Product line:	S5A
Technology:	AGM - Absorbent Glass Mat*
EAN code:	4047025244336





Technical information				
Nominal Voltage:	12 V			
Nominal capacity: (20 hr discharge down to 10.5 V)	C20	60 Ah		
Reserve capacity: (@ 25 A)				
Cold cranking amps: (EN / -18°C U10s ≥ 7.5 V)	680 A			
Group size:	LN2			
JIS type:	-			
Short-time angle of inclination:	360°			
Permanent angle of inclination:	up to 90°			
Dimension:	Length 242 mm	Width 175 mm	Ht. w/o terminal	Ht. w terminal 190 mm
Total battery weight: (approx., filled battery)	17,35 kg			
Layout: (ETN, DIN 72331)	0			
Terminal: (ETN, DIN 72331)	1			
Base hold down: (ETN, DIN 72331)	B13			
Degassing:	VRLA (Valve Regulated Lead Acid)			

Technical data		
Application:		Start/Stop
Service:		Maintenance-free
Standard charging:	Charging voltage: Charging current: Charging pattern:	14,8 V 6 A IU
European standards:		DIN EN 60095-1, -2, -4 Lead-acid starter batteries; DIN EN 50342 Lead-acid starter batteries; DIN 41 773, Charger with IU characteristics