


SLI Battery

For commercial vehicles



Part information

Part No:	0092T30320
Short code:	T3 032
Product line:	T3
Technology:	SLI - Starting-Lighting-Ignition*
EAN code:	4047024344822



Technical information

Nominal Voltage:	12 V			
Nominal capacity: (20 hr discharge down to 10.5 V)	C20	100 Ah		
Reserve capacity: (@ 25 A)				
Cold cranking amps: (EN / -18°C U10s ≥ 7.5 V)	720 A			
Group size:	GB28			
JIS type:	-			
Short-time angle of inclination:	55°			
Permanent angle of inclination:	0°			
Dimension:	Length 315 mm	Width 175mm	Ht. w/o terminal	Ht. w terminal 210 mm
Total battery weight: (approx., filled battery)	22,34 kg			
Layout: (ETN, DIN 72331)	0			
Terminal: (ETN, DIN 72331)	1			
Base hold down: (ETN, DIN 72331)	B03			
Degassing:	-			

Technical data

Application:		Conventional	
Service:		Maintenance-free	
Standard charging:	Charging voltage:	14,4 V	
	Charging current:	10 A	
	Charging pattern:	IU	
European standards:		DIN EN 60095-1, -2, -4 Lead-acid starter batteries; DIN EN 50342 Lead-acid starter batteries; DIN 41 773, Charger with IU characteristics	