


# SLI Battery For commercial vehicles



## Part information

|               |                                   |
|---------------|-----------------------------------|
| Part No:      | 0092T30401                        |
| Short code:   | T3 040                            |
| Product line: | T3                                |
| Technology:   | SLI - Starting-Lighting-Ignition* |
| EAN code:     | 4047026451511                     |



## Technical information

|                                                    |                  |                |                  |                          |
|----------------------------------------------------|------------------|----------------|------------------|--------------------------|
| Nominal Voltage:                                   | 12 V             |                |                  |                          |
| Nominal capacity: (20 hr discharge down to 10.5 V) | C20              | 125 Ah         |                  |                          |
| Reserve capacity: (@ 25 A)                         |                  |                |                  |                          |
| Cold cranking amps: (EN / -18°C U10s ≥ 7.5 V)      | 720 A            |                |                  |                          |
| Group size:                                        | D3               |                |                  |                          |
| JIS type:                                          | -                |                |                  |                          |
| Short-time angle of inclination:                   | 55°              |                |                  |                          |
| Permanent angle of inclination:                    | 0°               |                |                  |                          |
| Dimension:                                         | Length<br>344 mm | Width<br>172mm | Ht. w/o terminal | Ht. w terminal<br>285 mm |
| Total battery weight: (approx., filled battery)    | 31,22 kg         |                |                  |                          |
| Layout: (ETN, DIN 72331)                           | 0                |                |                  |                          |
| Terminal: (ETN, DIN 72331)                         | 1                |                |                  |                          |
| Base hold down: (ETN, DIN 72331)                   | B00              |                |                  |                          |
| Degassing:                                         | -                |                |                  |                          |

## Technical data

|                     |                   |                                                                                                                                                 |  |
|---------------------|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Application:        |                   | Conventional                                                                                                                                    |  |
| Service:            |                   | Maintenance-free                                                                                                                                |  |
| Standard charging:  | Charging voltage: | 14,4 V                                                                                                                                          |  |
|                     | Charging current: | 12,5 A                                                                                                                                          |  |
|                     | Charging pattern: | IU                                                                                                                                              |  |
| European standards: |                   | DIN EN 60095-1, -2, -4 Lead-acid starter batteries;<br>DIN EN 50342 Lead-acid starter batteries;<br>DIN 41 773, Charger with IU characteristics |  |